OFFICE OF NAVAL RESEARCH

GRANT No. N00014-93-1-1307

R & T Code: 4132098

Technical Report No. 22

FINAL REPORT: POLYANILINE MEMBRANES FOR SEPARATION APPLICATIONS

by

Richard B. Kaner

University of California, Los Angeles Department of Chemistry and Biochemistry 405 Hilgard Avenue Los Angeles, CA 90095-1569

Prepared for The Office of Naval Research.



Reproduction in whole or in part is permitted for any purpose of the United States Government. This document has been approved for public release and sale; its distribution is unlimited.

19980225 031

REPORT DOCUMENTATION PAGE

\$

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget. Paperwork Reduction Project (0704-0188), Washington, OC 20503.

1. AGENCY USE ONLY (Leave blan	k) 2. REPORT DATE Nov. 1, 1997	3. REPORT TYPE AND DAT Technical	EPORT TYPE AND DATES COVERED echnical	
4. TITLE AND SUBTITLE FINAL REPORT: POLYANILINE MEMBRANES FOR SEPARATION APPLICATIONS 5.			NDING NUMBERS RANT No. N00014-93-1-1307	
6. AUTHOR(S) Richard B. Kaner			& T Code: 4132098 r. Kenneth Wynne	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of California, Los Angeles Department of Chemistry and Biochemistry 405 Hilgard Avenue Los Angeles, CA 90095-1569			RFORMING ORGANIZATION PORT NUMBER 22	
9. SPONSORING/MONITORING AGE Department of the Navy Office of Naval Research 800 North Quincy Street Arlington, VA 22217-5660	NCY NAME(S) AND ADDRESS(ES	10. SF	ONSORING/MONITORING GENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Prepared for The Office of Nava	al Research.			
12a. DISTRIBUTION / AVAILABILITY S Reproduction in whole or in pa Government. This document h distribution is unlimited.	STATEMENT ort is permitted for any purpose o as been approved for public relea	f the United States	DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) High quality membranes of polyaniline/ethylaniline copolymers along with polyaniline/polyimide blends have been synthesized. Water permeates preferentially over organics (such as acetic acid) through doped polyaniline due to a combination of favorable diffusion and solubility. Fully doped polyaniline is among the most selective membranes yet developed for water/acetic acid separations: e.g. at 50% water/50% acetic acid the selectivity α is > 1,000. Fully doped polyaniline membranes are highly selective effectively blocking species with diameters ≥ 4.5 Å. In addition to traditional dopants, ion implantation has been found to be an effective method to produce very highly conductive polyaniline films which exhibit metallic-like behavior.				
14. SUBJECT TERMS Conducting Polymers, Polyaniline, Membrane, Gas Separation, Pervaporation			15. NUMBER OF PAGES 16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	UL	

ONR Final Report Grant No. N00014-93-1307

Objective and Approach:

A comprehensive study of dopable conjugated polymers as permselective membranes has been carried out. This work focused on the effects of dopants on the membranes' permeability and selectivity. Pervaporation, a process in which one component is separated from a mixture of liquids by selective transport through a membrane, will benefit from the ability to tailor a membrane's properties after formation; i.e. for polyaniline membranes, through the doping process using common acids and bases. Polyaniline is a model conjugated polymer because of its processibility, simple acid/base doping chemistry and air and thermal stability. Polyaniline membranes were first studied for individual solvent's permeation to gain fundamental information. Then mixtures, such as of several organic acids and water, were investigated. The effects of size and concentration of permeating acids on polyaniline films were examined. Further investigations involved separation of other organic/water mixtures and the effects of modified polyaniline membranes on pervaporation. These new membranes involved the synthesis of copolymers and blends of polyaniline. Increases in flux through polyaniline films are now being explored through increasing the operating temperature and by developing asymmetric hollow fiber membranes.

Conclusions

High quality membranes of polyaniline and polyaniline/ethylaniline copolymers along with polyaniline/polyimide blends have been synthesized. Water permeates preferentially over organics (such as acetic acid) through doped polyaniline due to a combination of favorable diffusion and solubility. Fully doped polyaniline is among the most selective membranes yet developed for water/acetic acid separations: e.g. at 50% water/50% acetic acid the selectivity α is >1000. Fully doped polyaniline membranes are highly selective effectively blocking species with diameters \geq 4.5Å. In addition to traditional dopants, ion implantation has been found to be an effective method to produce very highly conductive polyaniline films which exhibit metallic-like behavior.

Students Supported by ONR:

Graduate Students:		Undergraduates:	
1. Jeannine A. Conklin* (Ph.D. awarded 10/94)	1.	Song Nguyen*,	
2. Shu-Chuan Huang*,+ (Ph.D. awarded 1/95)	2.	Angela Kwon*,	
3. Tim S. Su ⁺ (Ph.D. awarded 7/96)	3.	David K. Kim+	
4. Ian Ball	4.	Belinda Lew*,+	
5. Rhonda Larson*	5.	Steve Luboviski	
	6.	Annise Berger*	
Postdoctoral Associates:		Kim Miller*,+	
1. Dr. Shu-Chuan Huang*,+	8.	Jim Shimano+	

^{* =} female; + = Asian

Publication Highlights:

- 1. *Macromolecules*, **28**, 6522 (1995).
- Block copolymers of aniline with ethylaniline have been synthesized and grown as high quality, free-standing films. The materials are thermally stable to above 400° C. The reactivity ratios for aniline and o-ethylaniline were determined to be 0.128 and 11.7, respectively. This results in long blocks of o-ethylaniline and short blocks of aniline. The greater the ethylaniline content of the copolymer, the higher the solubility in non-aqueous solvents. For example, whereas only 0.002g of pure polyaniline dissolved (technically dispersed) in 10 ml of tetrahydrofuran, with 47% and 84% ethylaniline, 0.048 g and \geq 0.250 g of copolymer dissolved.
- 2. Phys. Rev. B, 54, 11638 (1996).

In this paper, argon ions are implanted into high quality, free-standing polyaniline films. The resulting Ar^+ doped gold colored polymer has a conductivity of $800\Omega^{-1}cm^{-1}$, the highest room temperature conductivity reported so far. On cooling to 8K, this material shows metallic conductivity, a property not found in conventionally doped polyaniline which generally looks like a dirty metal. The metallic conductivity can be altered in a magnetic field of ≥ 2.7 Tesla. This work included a collaboration with the Naval Research Laboratory (see transition).

3. Handbook of Conducting Polymers, 2nd Edition (Dekker, 1997), pp. 945-961. This chapter describes in detail how high quality free-standing polyaniline membranes can be used for liquid and gas separations. Separation of water from organic mixtures using fully doped polyaniline membranes is demonstrated. Doped polyaniline has a remarkable ability to exclude organics with sizes $\geq 4.5 \text{\AA}$.

Presentation Highlights:

The first invitation to present our research on liquid separations using conjugated polymer membranes, at the 209th National Meeting of the American Chemical Society was likely the most memorable. A special symposium was devoted to applications of conjugated polymers and many colleagues in the field were impressed by the stability and possibilities for liquid separations using doped polyaniline membranes.

Award Highlights:

Belinda Lew, an undergraduate, was a Waldo Semon Research Award Finalist in Polymer Chemistry for her work on polyaniline membranes. She gave a presentation on her research and received the award at the University of Akron in Akron, Ohio. Belinda also earned the UCLA Ethel Terry McCoy Prize for excellence in Chemistry and graduated Phi Betal Kappa with Highest Honors. She is now a graduate student in chemistry at Harvard University.

Richard Kaner, the P.I., received a 1996-97 John Simon Guggenheim Foundation Fellowship for "distinguished achievement in the past and exceptional promise for future accomplishment." He was among the 158 scientists and artists chosen from 2,791 nominees.

Transition:

In the course of studying the effects on permeability through conjugated polymer membranes by changing dopants, the idea occurred to us of using ion implantation as the ultimate method of forming modified thin asymmetric membranes. Although the effects on permeability were modest, we did succeed in making the most highly conducting polyaniline films known to date with a room temperature conductivity of $800 \ \Omega^{-1} \text{cm}^{-1}$ (*Mat. Res. Soc. Symp. Proc.*, **413**, 609, 1996). These materials were among the first polyanilines to show metallic-like conductivity at low temperatures (300K-1.8K) (*Phys. Rev. B*, **54**, 11638, 1996). This work was carried out in collaboration with coworkers at the U.S. Naval Research Laboratory and at the A.F. Joffe Physico-Technicial Institute in St. Petersburg, Russia.

Richard B. Kaner

Publications Supported by ONR

- 1. J.A. Conklin, S.-C. Huang and R.B. Kaner, "Polyaniline Membranes for Gas and Liquid Separations," *Polym. Preprints*, **35**, 251 (1994).
- 2. J.A. Conklin, S.-M. Huang and R.B. Kaner, "Polyaniline and Poly(aniline-co-oethylaniline) Synthesis and Characterization," *Polym. Preprints*, **35**, 283 (1994).
- 3. J. Conklin and R.B. Kaner, "Diffusion Through Polymer Membranes," *The Encyclopedia of Advanced Materials*, D. Bloor, R.J. Brook, M.C. Flemings, and S. Mahajah, eds. (Pergamon Press, London, England, 1994) p. 1483.
- T.M. Su, S.-M. Huang, J.A. Conklin, D.K. Kim, S.J. Nguyen and R.B. Kaner, "Acid Diffusion Through Polyaniline Membranes," *Polym. Mater. Sci. Eng.*, **72**, 168 (1995).
- 5. S.-C. Huang, J.A. Conklin, T.M. Su, I.J. Ball, S.L. Nguyen, B.M. Lew and R.B. Kaner, "Synthesis, Pervaporation and Gas Separation Studies of Polyaniline Blends," *Polym. Mater. Sci. Eng.*, **72**, 323 (1995).
- 6. J.A. Conklin, M.R. Anderson, H. Reiss and R.B. Kaner, "Anhydrous Halogen Acid Doping of Polyaniline Films and Its Effect on Permeability," *Polym. Mater. Sci. Eng.*, 72, 313 (1995).
- 7. J. Conklin, S.-C. Huang, S.-M. Huang, T. Wen and R.B. Kaner, "Thermal Properties of Polyaniline and Poly(aniline-co-o-ethylaniline)," *Macromolecules*, **28**, 6522 (1995).
- 8. T.M. Su, A.H. Kwon, B.M. Lew and R.B. Kaner, "Synthesis and Gas Separation Studies of Substituted Polyaniline Membranes," *Polym. Preprints*, **37**, 670 (1996).
- 9. I.J. Ball, S.-C. Huang, T.M. Su, A.P. Berger and R.B. Kaner, "Permeability and Solubility Processes in Polyaniline Membranes," *Polym. Preprints*, **37**, 672 (1996).
- 10. J.A. Conklin, M.R. Anderson, H. Reiss and R.B. Kaner, "Anhydrous Halogen Acid Interaction with Polyaniline Membranes: A Gas Permeability Study," *J. Phys. Chem.*, **100**, 8425 (1996).
- 11. A.N. Aleshin, N.B. Mironkov, A.V. Suvorov, J.A. Conklin, T.M. Su and R.B. Kaner, "Electrical Properties of Ion Implanted and Chemically Doped Polyaniline Films," *Mat. Res. Soc. Symp.*, **413**, 609 (1996).
- 12. A.N. Aleshin, N.B. Mironkov, A.V. Suvorov, J.A. Conklin, T.M. Su and R.B. Kaner, "Transport Properties of Ion Implanted and Chemically Doped Polyaniline Films," *Phys. Rev. B*, **54**, 11638 (1996).
- 13. A.N. Aleshin, N.B. Mironkov and R.B. Kaner, "Low-temperature conductivity and magnetoresistance of ion-irradiated polyaniline on the metal side of the metal-insulator transition," *Phys. Solid State*, **38**, 1738 (1996).
- 14. A.H. Kwon, J.A.Conklin, M. Makhinson and R.B. Kaner, "Chemical Syntheses and Characterization of Fluoro-Substituted Polyanilines," *Synthetic Metals*, **84**, 95 (1997).
- 15. A.N. Aleshin, N.B. Mironkov and R.B. Kaner, "The Influence of Weak Localization and Coulomb Interaction on the Low Temperature Resistance and Magnetoresistance on Ion Implanted Metallic Polyaniline Films," *Synthetic Metals*, **84**, 769 (1997).
- 16. I.J. Ball, S.-C. Huang, T.M. Su and R.B. Kaner, "Permselectivity and Temperature-Dependent Permeability of Polyaniline Membranes," *Synthetic Metals*, **84**, 799 (1997).
- 17. T.M. Su, I.J. Ball, J.A. Conklin, S.-C. Huang, R.K. Larson, S.N. Nguyen, B.M. Lew and R.B. Kaner, "Polyaniline/Polyimide Blends for Pervaporation and Gas Separation Studies," *Synthetic Metals*, **84**, 801 (1997).
- 18. J.A. Conklin, S.-C. Huang, T.M. Su and R.B. Kaner, "Gas and Liquid Separation Applications of Polyaniline Membranes," in *Handbook of Conducting Polymers 2nd Edition*, J. Reynolds, T. Skotheim and R. Elsenbaumer, eds. (Marcel Dekker, Inc., New York, 1997), pp. 945-961.